

IN-PLANT LIFT TABLES

for every application



SCISSOR LIFT TABLES | TILTERS AND UPENDERS | TURN TABLES

In-Plant Lift Tables CONTENTS

Scissor Lift Tables

	Standard Duty Scissor	1
	Wide Base Scissor	2
	Double Wide Scissor	3
	Tandem Long Scissor	4
	Double Scissor	5
	Zero Ground Level Scissor	6
	Pneumatic Scissor	7
	ers and Upenders	
H	Hydraulic Tilters	8
	Nide Base Hydraulic Tilters	9
l	Jpenders	10
F	Pneumatic Tilt	11
Tur	n Tables	12

Standard Duty Scissor

Blue Giant Standard Duty Series Scissor Lift Tables are economical, have a heavy-duty design, and are built to improve operator ergonomics and enhance productivity. With vertical travel ranges from 24" (610 mm) to 60" (1,524 mm) and lifting capacities of up to 6,000 lbs (2,721 kg), these units will meet all of your application requirements.

FEATURES

- · Heavy-duty cylinders
- Heavy-duty steel legs
- Internal power units
- · Lifetime lubricated bearings
- Safety maintenance blocks
- Standard hand controls
- Travel limit switch

OPTIONS

- Accordion skirts
- Conveyor
- External power unit
- Foot pedal control
- High cycle
- Oversized platform
- PLC controlled
- Pit mounted
- Platform with beveled edges
- Portability package
- Tilt table mounted to lift
- Turn table mounted to lift



SPECIFICATIONS

Model Number	Load Capacity	Lowered Height	Raised Height	Standard Platform	Maximum Platform	Standard Motor
LFT24 SER	IES – 24" TRAVEL					
LFT24-20	2,000 lbs (907 kg)					1 HP
LFT24-20	4,000 lbs (1,814 kg)	7.5" (191 mm)	31.5" (800 mm)	24" x 36" (610 x 914 mm)	48" x 60" (1,219 x 1,524 mm)	Inr
LFT24-60	6,000 lbs (2,721 kg)	,		,	,	2 HP*
LFT36 SER	IES – 36" TRAVEL					
LFT36-20	2,000 lbs (907 kg)					1 HP
LFT36-40	4,000 lbs (1,814 kg)	7.5" (191 mm)	43.5" (1,105 mm)	24" x 48" (610 x 1,219 mm)	48" x 72" (1,219 x 1,829 mm)	Inr
LFT36-60	6,000 lbs (2,721 kg)	,				2 HP*
LFT48 SER	IES – 48" TRAVEL					
LFT48-20	2,000 lbs (907 kg)					1 HP
LFT48-40	4,000 lbs (1,814 kg)	7.5" (191 mm)	55.5" (1,410 mm)	24" x 64" (610 x 1,626 mm)	48" x 96" (1,219 x 2,438 mm)	Inr
LFT48-60	6,000 lbs (2,721 kg)	,	(1,113)	,		2 HP*
LFT60 SER	LFT60 SERIES - 60" TRAVEL					
LFT60-20	2,000 lbs (907 kg)					1 HP
LFT60-40	4,000 lbs (1,814 kg)	10" (254 mm)	70" (1,778 mm)	24" x 88" (610 x 2,235 mm)	48" x 120" m) (1,219 x 3,048 mm)	Inr
LFT60-60	6,000 lbs (2,721 kg)	, ,	, , , , , ,	, , ,	, , , , ,	2 HP*

*6,000 lb units come standard with external power unit.

Wide Base Scissor

Blue Giant Wide Base Series Scissor Lift Tables are cost-effective and ergonomically designed to meet all your application requirements. The wide base provides enhanced stability and support to handle larger loads of up to 6,000 lbs (2,721 kg).

FEATURES

- Heavy-duty cylinders
- Heavy-duty steel legs
- Internal power units
- Lifetime lubricated bearings
- Safety maintenance blocks
- Standard hand controls
- Travel limit switch

- **OPTIONS**
- Accordion skirts
- Conveyor
- External power unit
- Foot pedal control
- High cycle
- Oversized platform
- PLC controlled
- Pit mounted
- Platform with beveled edges
- Portability package
- Tilt table mounted to lift
- Turn table mounted to lift



SPECIFICATIONS

Model Number	Load Capacity	Lowered Height	Raised Height	Standard Platform	Maximum Platform	Standard Motor
LFTWB24 S	SERIES – 24" TRAVE	L				
LFTWB24-20	2,000 lbs (907 kg)					4.115
LFTWB24-40	4,000 lbs (1,814 kg)	7.5" (191 mm)	31.5" (800 mm)	36" x 36" (914 x 914 mm)	60" x 60" (1524 x 1524 mm)	1 HP
LFTWB24-60	6,000 lbs (2,721 kg)	()	(555)	(6 6)	(102174102111111)	2 HP*
LFTWB36 S	SERIES – 36" TRAVE	L				
LFTWB36-20	2,000 lbs (907 kg)					4.115
LFTWB36-40	4,000 lbs (1,814 kg)	7.5" (191 mm)	43.5" (1,105 mm)	36" x 48" (914 x 1,219 mm)	60" x 72" (1524 x 1,829 mm)	1 HP
LFTWB36-60	6,000 lbs (2,721 kg)	()	(1,133 1111)	(0 ,	(1021 X 1,020 11111)	2 HP*
LFTWB48 S	SERIES – 48" TRAVE	L				
LFTWB48-20	2,000 lbs (907 kg)					1 HP
LFTWB48-40	4,000 lbs (1,814 kg)	7.5" (191 mm)	55.5" (1,410 mm)	36" x 64" (914 x 1,626 mm)	60" x 96" (1524 x 2,438 mm)	1116
LFTWB48-60	6,000 lbs (2,721 kg)	()				2 HP*
LFTXB36 S	ERIES – 36" TRAVEL	-				
LFTXB36-20	2,000 lbs (907 kg)					4 UD
LFTXB36-40	4,000 lbs (1,814 kg)	7.5" (191 mm)	43.5" (1,105 mm)	36" x 48" (914 x 1,219 mm)	60" x 72" (1524 x 1,829 mm)	1 HP
LFTXB36-60	6,000 lbs (2,721 kg)	,				2 HP*
LFTXB48 S	ERIES – 48" TRAVEL					
LFTXB48-20	2,000 lbs (907 kg)					4.110
LFTXB48-40	4,000 lbs (1,814 kg)	7.5" (191 mm)	55.5" (1,410 mm)	48" x 64" (1,219 x 1,626 mm)	72" x 96" (1,829 x 2,438 mm)	1 HP
LFTXB48-60	6,000 lbs (2,721 kg)	()	(1,11011111)	(1,210 % 1,020 11111)	(1,020 % 2, 100 11111)	2 HP*
LFTXB60 S	ERIES – 60" TRAVEL					
LFTXB60-20	2,000 lbs (907 kg)					4.110
LFTXB60-40	4,000 lbs (1,814 kg)	10" (254 mm)	70" (1,778 mm)	56" x 88" (1,422 x 2,235 mm)	84" x 120" nm) (2,134 mm x 3,048 mm)	1 HP
LFTXB60-60	6,000 lbs (2,721 kg)	(== :)	(1,110111111)			2 HP*

*6,000 lbs units come standard with external power unit.

Double Wide Scissor

Blue Giant Double Wide Series Scissor Lift Tables provide enhanced load stability and support. It's heavy-duty design allows for higher load capacities ranging from 2,000 lbs (907 kg) to 6,000 lbs (2,722 kg). With vertical travel ranging from 24" to 60" (610 mm x 1,524 mm), these units are built to meet all your application requirements.

FEATURES

- · Heavy-duty cylinders
- Heavy-duty steel legs
- Internal power units
- · Lifetime lubricated bearings
- Safety maintenance blocks
- Standard hand controls

OPTIONS

- Accordion skirts
- Conveyor
- External power unit
- Foot pedal control
- High cycle
- Custom sized platform
- PLC controlled
- Pit mounted
- Platform with beveled edges
- Portability package
- Tilt table mounted to lift
- Travel limit switch
- Turn table mounted to lift



SPECIFICATIONS

Model Number	Load Capacity	Lowered Height	Raised Height	Standard Platform	Maximum Platform	Standard Motor
LFTDW24 SE	RIES – 24" TRAVEL					
LFTDW24-40	4,000 lbs (1,814 kg)					4 110
LFTDW24-80	8,000 lbs (3,629 kg)	7.5" (191 mm)	31.5" (800 mm)	48" x 36" (1,219 x 914 mm)	72" x 60" (1,829 x 1,524 mm)	1 HP
LFTDW24-120	12,000 lbs (5,443 kg)		, ,	,	,	2 HP*
LFTDW36 SE	RIES – 36" TRAVEL					
LFTDW36-40	4,000 lbs (1,814 kg)					4 LID
LFTDW36-80	8,000 lbs (3,629 kg)	7.5" (191 mm)	43.5" (1,105 mm)	48" x 48" (1,219 x 1,219 mm)	72" x 72" (1,829 x 1,829 mm)	1 HP
LFTDW36-120	12,000 lbs (5,443 kg)					2 HP*
LFTDW48 SE	RIES – 48" TRAVEL					
LFTDW48-40	4,000 lbs (1,814 kg)					4 LID
LFTDW48-80	8,000 lbs (3,629 kg)	7.5" (191 mm)	55.5" (1,410 mm)	48" x 64" (1,219 x 1,626 mm)	72" x 96" (1,829 x 2,438 mm)	1 HP
LFTDW48-120	12,000 lbs (5,443 kg)			,		2 HP*
LFTDW60 SE	LFTDW60 SERIES – 60" TRAVEL					
LFTDW60-40	4,000 lbs (1,814 kg)					4 HD
LFTDW60-80	8,000 lbs (3,629 kg)	10" (254 mm)	70" (1,778 mm)	48" x 88" (1,219 x 2,235 mm)		1 HP
LFTDW60-120	12,000 lbs (5,443 kg)	, ,	(1,773 11111)			2 HP*

*12,000 lb units come standard with external power unit.

Tandem Long Scissor

Blue Giant Tandem Scissor Lift Tables are heavy-duty, hydraulic scissor lift tables for applications requiring longer platform sizes. These lift tables feature a longer length platform to meet the application needs of manufacturing, processing and distribution operations where materials of greater length are being handled.

FEATURES

- · Heavy-duty cylinders
- Heavy-duty steel legs
- Internal power units
- Lifetime lubricated bushings
- Safety maintenance blocks
- Standard hand controls

OPTIONS

- Accordion skirts
- Conveyor
- External power unit
- Foot pedal control
- High cycle
- Custom sized platform
- PLC controlled
- Pit mounted
- Platform with beveled edges
- Portability package
- Tilt table mounted to lift
- Travel limit switch
- Turn table mounted to lift



SPECIFICATIONS

Model Number	Load Capacity	Lowered Height	Raised Height	Standard Platform	Maximum Platform	Standard Motor
LFTDL24 SEF	RIES – 24" TRAVEL					
LFTDL24-40	4,000 lbs (1,814 kg)					1 HP
LFTDL24-80	8,000 lbs (3,629 kg)	7.5" (191 mm)	31.5" (800 mm)	24" x 72" (610 x 1,829 mm)	48" x 120" (1,219 x 3,048 mm)	Inp
LFTDL24-120	12,000 lbs (5,443 kg)		, ,	,	,	2 HP*
LFTDL36 SEF	RIES – 36" TRAVEL					
LFTDL36-40	4,000 lbs (1,814 kg)					1 HP
LFTDL36-80	8,000 lbs (3,629 kg)	7.5" (191 mm)	43.5" (1,105 mm)	24" x 96" (610 x 2,438 mm)	48" x 144" (1,219 x 3,658 mm)	Inr
LFTDL36-120	12,000 lbs (5,443 kg)					2 HP*
LFTDL48 SEF	RIES – 48" TRAVEL					
LFTDL48-40	4,000 lbs (1,814 kg)					1 HP
LFTDL48-80	8,000 lbs (3,629 kg)	7.5" (191 mm)	55.5" (1,410 mm)	24" x 128" (610 x 3,251 mm)	48" x 176" (1,219 x 3,251 mm)	I THE
LFTDL48-120	12,000 lbs (5,443 kg)		,			2 HP*
LFTDL60 SEF	LFTDL60 SERIES – 60" TRAVEL					
LFTDL60-40	4,000 lbs (1,814 kg)					1 HP
LFTDL60-80	8,000 lbs (3,629 kg)	10" (254 mm)	70" (1,778 mm)	24" x 176" (610 x 4,470 mm)	48" x 220" (1,219 x 5,588 mm)	Inr
LFTDL60-120	12,000 lbs (5,443 kg)	,	(1,77011111)	,	(1,210 / 0,000 11111)	2 HP*

*6,000 lb units come standard with external power unit.

Double Scissor

Blue Giant Double Scissor Lift Tables are a safe and efficient solution for in-plant product storage and transfer. The same high quality construction features found in the stationary elevating docks are incorporated into all scissor lifts. Each lift cylinder is encased in a weather-resistant, all steel housing. Precision velocity fuses on each hydraulic cylinder eliminates platform free-fall. All hard chromed pivot points are fitted with lifetime-lubricated bronze bearings or TeflanTM coated bushings.

FEATURES

- Scissor lifts can be mounted in a pit or a concrete pad
- Remote power pack 12' (3,658 mm) hydraulic hose
- Push button control on 12' (3,658 mm) straight cord
- Hydraulic pump with built-in overload relief
- All hydraulic components including hoses and oil

OPTIONS

- · Custom sizes and designs
- Lips or bridge plates
- · Electrical trip bars
- Self-contained or larger HP power packs
- Foot pedal control

- Guard rails
- · Checker deck surfaces
- Travel limit switch
- Portable wheels
- Accordion safety skirting



Model Number	Load Capacity	Lowered Height	Raised Height	Standard Platform	Maximum Platform	Standard Motor	
DS48 SERI	ES - 48" TRAVEL						
DS1-48	1,000 (454 kg)						
DS2-48	2,000 (907 kg)	12"	60"	24" x 48"	48" x 48"	O LID	
DS3-48	3,000 (1,361 kg)	(305 mm)	(1,524 mm)	(610 x 1,219 mm)	(1,219 x 1,219 mm)	3 HP	
DS4-48	4,000 (1,814 kg)						
DS60 SERI	DS60 SERIES - 60" TRAVEL						
DS1-60	1,000 (454 kg)			24" x 60" (610 x 1,524 mm)	48" x 60" (1,219 x 1,524 mm)	3 HP	
DS2-60	2,000 (907 kg)	12"					
DS3-60	3,000 (1,361 kg)	(305 mm)					
DS4-60	4,000 (1,814 kg)						
DS72 SERI	ES - 72" TRAVEL						
DS1-72	1,000 (454 kg)						
DS2-72	2,000 (907 kg)	12"	84"	24" x 72"	48" x 72"	0.115	
DS3-72	3,000 (1,361 kg)	(305 mm)	(2,134 mm)	(610 x 1,829 mm)	(1,219 x 1,829 mm)	3 HP	
DS4-72	4,000 (1,814 kg)						

Zero Ground Level Scissor

Blue Giant Zero Ground Level Scissor Lifts are designed for use when powered fork trucks are not available or accessible in a work area. These tables permit floor level loading / unloading access by pallet jacks and other material handling equipment. The front approach edge of the platform is beveled to make loading / unloading of the table an easy operation.

FEATURES

- External power units
- · Heavy-duty cylinders
- Heavy-duty steel legs
- · Lifetime lubricated bearings
- Safety maintenance blocks
- Standard hand controls
- 6" (152 mm) flexible safety toe guard

OPTIONS

- Accordion skirts
- Conveyors
- Foot pedal control
- Oversized platforms
- PLC controlled



Model Number	Load Capacity	Platform Size	Overall Dimensions	Lowered Height	Standard Motor
ZPL-20 SERIES LIFTS – 3	6" TRAVEL				
ZPL-20-4448	2 000 lbs (007 kg)	44" x 48" (1,118 x 1,219 mm)	64" x 56" (1,626 x 1,422 mm)	2/0" (10 mm)	4 LID
ZPL-20-5048	2,000 lbs (907 kg)	50" x 48" (1,270 x 1,219 mm)	70" x 56" (1,778 x 1,422 mm)	- 3/8" (10 mm)	1 HP
ZPL-40 SERIES LIFTS – 3	6" TRAVEL				
ZPL-40-4448	4 000 lbc (4 044 lbc)	44" x 48" (1,118 x 1,219 mm)	64" x 56" (1,626 x 1,422 mm)	4 (011 (4.0	4 110
ZPL-40-5048	4,000 lbs (1,814 kg)	50" x 48" (1,270 x 1,219 mm)	70" x 56" (1,778 x 1,422 mm)	1/2" (13 mm)	1 HP

Pneumatic Scissor

Blue Giant's complete line of heavy-duty industrial Pneumatic Scissor Lift Tables are 100% air actuated and can be used anywhere plant air is available. These units are ideal in applications where hydraulic equipment (oils and fluids) is prohibited. These units require less maintenance than electric hydraulic units with no direct electrical connections, control boxes, or hydraulic cylinders. The Pneumatic Tables feature 24" (610 mm) vertical travel, 33.5" (851 mm) raised height with 9.5" (241 mm) lowered height.

FEATURES

- · Heavy-duty air spring
- Heavy-duty steel legs
- Lifetime lubricated bearings
- Safety maintenance block
- Standard hand controls

OPTIONS

- Accordion skirts
- Conveyor
- Detent stops
- Oversized platforms
- Pit mounted unit
- Platform with beveled edges
- Portability package
- Stainless steel
- Tilt tables mounted to lifts
- Turn tables



Model Number	Load Capacity	Platform Size
AF24-10 SERIES		
AF24-10-3648		36" w x 48" h (914 x 1,219 mm)
AF24-10-4848	4 000 lb - (454 b -)	48" w x 48" h (1,219 x 1,219 mm)
AF24-10-4856	1,000 lbs (454 kg)	48" w x 56" h (1,219 x 1,422 mm)
AF24-10-4860		48" w x 60" h (1,219 x 1,524 mm)
AF24-20 SERIES		
AF24-20-3648		36" w x 48" h (914 x 1,219 mm)
AF24-20-4848	0.000 - (007 -)	48" w x 48" h (1,219 x 1,219 mm)
AF24-20-4856	2,000 lbs (907 kg)	48" w x 56" h (1,219 x 1,422 mm)
AF24-20-4860		48" w x 60" h (1,219 x 1,524 mm)
AF24-40 SERIES		
AF24-40-3648		36" w x 48" h (914 x 1,219 mm)
AF24-40-4848		48" w x 48" h (1,219 x 1,219 mm)
AF24-40-4856	4,000 lbs (1,814 kg)	48" w x 56" h (1,219 x 1,422 mm)
AF24-40-4860		48" w x 60" h (1,219 x 1,524 mm)

Hydraulic Tilters

Blue Giant Hydraulic Tilters come with a standard 8" or 12" (203 x 305 mm) lowered height depending on the tilt angle, and a standard base and platform of 36" x 48" (914 x 1,219 mm) (maximum platform size available is 48" x 60"). They also have an easily accessible internal power unit, as well as lifetime lubricated bushings at all pivot points. Oversized and custom sizes are available as well.

FEATURES

- 8" lip standard
- Easily accessible internal power units
- Heavy-duty cylinders
- · Lifetime lubricated bearings
- Standard hand controls

OPTIONS

- Accordion skirts
- Conveyor
- · Customized lips
- External power unit
- Oversized platform
- PLC controlled
- Foot pedal control
- · Portability package
- Travel limit switch



Model Number	Tilt Capacity	Lowered Height	Platform Size	Standard Motor
ETT30 SERIES	- 30° STANDARD TILT			
ETT30-20	2,000 lbs (907 kg)			1 HP
ETT30-40	4,000 lbs (1,814 kg)	8" 36" x 48" (914 x 1,219 mm) (203 mm) up to 48" x 60" (1,219 x 1,524 mm)		INF
ETT30-60	6,000 lbs (2,721 kg)		ap to 10 x 60 (1,210 x 1,02 1 min)	
ETT45 SERIES	- 45° STANDARD TILT			
ETT45-20	2,000 lbs (907 kg)			1 HP
ETT45-40	4,000 lbs (1,814 kg)	8" (203 mm)	36" x 48" (914 x 1,219 mm) up to 48" x 60" (1,219 x 1,524 mm)	INF
ETT45-60	6,000 lbs (2,721 kg)			2 HP
ETT90 SERIES	- 90° STANDARD TILT			
ETT90-20	2,000 lbs (907 kg)			4.115
ETT90-40	4,000 lbs (1,814 kg)	12" (305 mm)	36" x 48" (914 x 1,219 mm) up to 48" x 60" (1,219 x 1,524 mm)	1 HP
ETT90-60	6,000 lbs (2,721 kg)		(,=::::,==:::::,	2 HP

Wide Base Hydraulic Tilters

Blue Giant Wide Base Hydraulic Tilters are manufactured with the same specifications as the standard except the 90° standard tilt has a 12" (305 mm) lowered height, 60° x 60° (1,524 x 1,524 mm) standard base and platform, and 120° x 120° (3,048 x 3,048 mm) maximum platform. Oversized and custom sizes are also available.

FEATURES

- 8" lip standard
- · Easily accessible internal power units
- Heavy-duty cylinders
- · Lifetime lubricated bearings
- Standard hand controls

OPTIONS

- Accordion skirts
- Conveyor
- Customized lips
- External power unit
- Oversized platform
- PLC controlled
- Foot pedal control
- Portability package
- · Travel limit switch



Model Number	Tilt Capacity	Standard Motor	
WBETT45 SERI			
WBETT45-20	2,000 lbs (907 kg)	1 HP	
WBETT45-40	4,000 lbs (1,814 kg)	THE	
WBETT45-60	6,000 lbs (2,721 kg)	2 HP	
WBETT60 SERI	ES – 60° STANDARD TILT		
WBETT60-20	2,000 lbs (907 kg)	1 HP	
WBETT60-40	4,000 lbs (1,814 kg)	INF	
WBETT60-60	6,000 lbs (2,721 kg)	2 HP	
WBETT90 SERI	ES – 90° STANDARD TILT		
WBETT90-20	2,000 lbs (907 kg)	4.115	
WBETT90-40	4,000 lbs (1,814 kg)	1 HP	
WBETT90-60	6,000 lbs (2,721 kg)	2 HP	

Upenders

Blue Giant manufactures a complete line of Hydraulic Upenders to accommodate most industrial needs. Our 90° Upenders are ideal for the safe re-positioning of pallet loads and odd shaped objects such as rolls or coils. Conveyors and V-Cradles can be mounted to the platform to assist with pallet, crate, and roll or coil positioning.

FEATURES

- 0° to 90° tilt angle
- · Heavy-duty cylinders
- Standard hand control for lowering / raising tilt

OPTIONS

- Accordion skirts
- Foot control
- · Oversized platforms
- PLC controlled
- Remote power units
- Roller conveyors
- V-Cradles
- · Custom sizes available



SPECIFICATIONS

Model Number	Load Capacity	Lowered Height
HUE SERIES - 9	90° TILT	
HUE-20-90	2,000 lbs (907 kg)	
HUE-40-90	4,000 lbs (1,814 kg)	12"
HUE-60-90	6,000 lbs (2,721 kg)	

 $\begin{tabular}{ll} \textbf{Upper Platform:} & 24" width x 36" length (609 x 914 mm) to 72" width x 96" length (1,829 x 2,438 mm) \\ \textbf{Lower Platform:} & 24" width x 36" length (609 x 914 mm) to 72" width x 96" length (1,829 x 2,438 mm) \\ \end{tabular}$

Pneumatic Tilt

Blue Giant's complete line of heavy-duty industrial Pneumatic Tilt Tables are 100% air actuated and can be used anywhere plant air is available. These units are ideal in applications where hydraulic equipment (oils and fluids) is prohibited. These units require less maintenance than electric hydraulic units with no direct electrical connections, control boxes, or hydraulic cylinders. The Pneumatic Tilt Tables feature 30° and 45° of tilt and 8" (203 mm) lowered height.

FEATURES

- 30° and 45° of tilt
- 8" (203 mm) lowered height
- Hand control pendant station
- Heavy-duty industrial air spring
- Integral flip up maintenance safety bars
- Lifetime lubricated bushings

OPTIONS

- Accordion skirts
- Conveyor
- · Custom platforms
- Floor stands
- Foot controller



Model Number	Load Capacity	Platform Size
AFT10 SERIES		
AFT10-3648		36" x 48" (914 x 1,219 mm)
AFT10-4848	4 000 (454)	48" x 48" (1,219 x 1,219 mm)
AFT10-4856	1,000 lbs (454 kg)	48" x 56" (1,219 x 1,422 mm)
AFT10-4860	-	48" x 60" (1,219 x 1,524 mm)
AFT20 SERIES		
AFT20-3648		36" x 48" (914 x 1,219 mm)
AFT20-4848	0.000 (007)	48" x 48" (1,219 x 1,219 mm)
AFT20-4856	2,000 lbs (907 kg)	48" x 56" (1,219 x 1,422 mm)
AFT20-4860		48" x 60" (1,219 x 1,524 mm)
AFT40 SERIES		
AFT40-3648		36" x 48" (914 x 1,219 mm)
AFT40-4856	4,000 lbs (1,814 kg)	48" x 56" (1,219 x 1,422 mm)
AFT40-4860		48" x 60" (1,219 x 1,524 mm)

Turn Tables

The Blue Giant Manual Turn Lift Table is designed to enhance operator ergonomics and productivity, by reducing the necessity to reach across, or walk around a load. These units are ideal in applications that require pallet loading or pallet unloading. 90° to 180° detents can be added to increase operator efficiency.

FEATURES

- 1/2" (13 mm) thick platform
- 4,000 lb (1,814 kg) load capacity
- Heavy-duty construction
- Lifetime lubricated kingpin bearings
- Low profile

OPTIONS

- 90° or 180° detents
- Conveyor mounted to top
- Floor / stand / scissor lift mounted



Model Number	Load Capacity	Platform Size	Load Capacity
MANUAL TURN TABLES			
MTT40-2424	4,000 lbs (1,814 kg)	24" x 24" (610 x 610 mm)	3" (76 mm)
MTT40-2436		24" x 36" (610 x 914 mm)	
MTT40-3636		36" x 36" (914 x 914 mm)	
MTT40-3648		36" x 48" (914 x 1,219 mm)	
MTT40-4848		48" x 48" (1,219 x 1,219 mm)	
MTT40-4860		48" x 60" (1,219 x 1,524 mm)	
MTT40-6060		60" x 60" (1.524 x 1,524 mm)	



Corporate 410 Admiral Blvd Mississauga, ON, Canada L5T 2N6 t 905.457.3900 f 905.457.2313 **USA** 6350 Burnt Poplar Road Greensboro, NC 27409 www.bluegiant.com

Blue Giant offers a full line of dock levelers, dock safety equipment, seals and shelters, accessories, ergonomic and scissor lift equipment and industrial trucks. Concurrent with our continuing product improvement program, specifications are subject to change without notice. Please contact Blue Giant for latest information. Some features illustrated may be optional in certain market areas.